STOWERS INDUSTRIAL POWER

CONTACT MARCIA GALLO AT 423-240-7850
OR MARK MILLER AT 865-595-1037

RENTAL FLEET SPECIFICATIONS

GENERATOR SETS

Model	kW Rating (Standby/Prime)	Output Voltage (VAC)	Mounting/Enclosure Type	Fuel Capacity (US gallons)	Fuel Usage/Hr @100% Load (US gallons)
XQ30	30/27	120/208-277/480	Trailer, Sound Attenuated	58	2.6
XQ60	60/54	120/208-277/480	Trailer, Sound Attenuated	149	5.1
XQ100	100/90	120/208-277/480	Trailer, Sound Attenuated	193	8
XQ125	125/113	120/208-277/480	Trailer, Sound Attenuated	140	9.9
XQ175	175/157	120/208-277/480	Trailer, Sound Attenuated	264	13.9
XQ230	230/210	120/208-277/480	Trailer, Sound Attenuated	400	18.3
XQ300	300/275	120/208-277/480	Trailer, Sound Attenuated	400	23.5
XQ400	400/365	120/208-277/480	Trailer, Sound Attenuated	470	31.9
XQ500	500/455	120/208-277/480	20' ISO, Sound Attenuated	600	36.3
C32/1000	1000	480 ONLY	30' ISO, Standard	800	72.5
3512/1250	1250/1100	480 ONLY	40' ISO, Standard	1250	88.2
XQ1750	1750/1600	480 ONLY	40' ISO,Sound Attenuated	1250	133.4
XQ2000	2000/1825	480 ONLY	40' ISO,Sound Attenuated	1250	140

CABLES AND DISTRIBUTION

Item	Configuration	Size	Description	Set Size
Load Cables	50' Each	4/0	Camlock Ends	
Cable Pigtails	6' Each	4/0	Camlock 1 end	5 Pieces Per Set
Distribution Panel	Holds 8 Twist Locks		Panel	
Quad Connectors	90' Each		3 Box String (12 Outlets Total)	
Cable Ramps			5 Slots Each Ramp - 4/0 Cable	
Extension Cables	100' Each			

NOTES:

- Fuel consumption is measured at full load condition. Fuel usage will vary according to load.
- Be sure generator set is set to proper voltage before making any connections.
- Other sizes and configurations of equipment are available upon request.
- Specifications are typical and subject to change.